

VACUUM & WINDSHIELD WASHER TUBING

For a Complete Listing of Barbed Brass Fittings See Page 238.


 Meets SAE J1037 Type 2 Specifications • EPDM Rubber Packed in coils of 25 and 50 ft. lengths

	Auveco Part No.	I.D.	O.D.	Unit Pkg.
Provide Barris Market Party Party	4453	7/64"		Fits 1/8" Nipple25'
A REAL PROPERTY AND A REAL PROPERTY AND A REAL PROPERTY.				Fits 1/8" Nipple50'
				Fits 3/16" Nipple25'
	4457	5/32"	5/16"	Fits 3/16" Nipple50'
	4459	7/32"	13/32"	Fits 1/4" Nipple25'
				Fits 1/4" Nipple50'
	4462	9/32"	15/32"	Fits 5/16" Nipple25'
	4463	9/32"	15/32"	Fits 5/16" Nipple50'

Fuel Line Hose

(Not For Electronic Fuel Injection) For a Complete Listing of Barbed Brass Fittings See Page 238.

- Meets the following O.E.M. Specifications: (GM: 6165-M) (SAE J30R7) (Chrysler MSEA219)
- Packaged in coils of 25 and 50 ft. lengths



Auveco Hose is designed for gas and diesel fuel lines (except Electronic Fuel Injection), emission control devices, and crankcase ventilation. In addition to the automotive applications, this hose is widely used on lawn mowers, marine motors, tractors and construction equipment to mention only a very few.

Auveco Part No.	Size	Working Pressure	
4464	1/4" I.D. x 1/2" O.D	50 PSI	25'
4465	1/4" I.D. x 1/2" O.D	50 PSI	50'
	5/16" I.D. x 9/16" O.D		
4467		50 PSI	50'

Electronic Fuel Injection Hose

- Meets or exceeds SAE 30R9 specifications.
- Quality fluoroelastomer tube and CM cover handles virtually every fuel on the market. Burst strength exceeds 900 PSI.

180 PSI wo Auveco Part No.	size	Unit Pkg.	Use With Auveco Clamp No.
19272	1/4" I.D. x 1/2" O.D 5/16 I.D. x 9//16" O.D 3/8" I.D. x 5/8" O.D	10 Ft	15861



20900 Hose Cutter

Razor sharp blade cleanly cuts heater hoses, fuel line hoses and any other type of flexible hose up to 1-1/4" diameter. The stainless steel blade is reversible for double the life. The pliers are made of glass-filled gray nylon for strength. Includes a locking hoop for safe storage. Overall length: 9-1/2"

UNIT PACKAGE: 1

