






## 1/4" Female Fully Insulated Nylon Piggyback Terminals


Actual Size	Wire Range	Auveco Part No.	Unit Pkg.
	22-18 Ga. 1/4" Tab Std. Barrel (Red)	<b>19298</b>	15
	16-14 Ga. 1/4" Tab Std. Barrel (Blue)	<b>19299</b>	15
	12-10 Ga. 1/4" Tab Std. Barrel (Yellow)	<b>19300</b>	15

### Fully Insulated Tap-Disconnect


	Wire Range	Auveco Part No.	Unit Pkg.
  Mates with 11828, 11605 & 11830	22-18 Ga. (Red)	<b>12791</b>	10
	18-14 Ga. (Blue)	<b>12161</b> <b>14898</b> <b>14899</b>	10 100 500
	12 Ga. (Yellow)	<b>12792</b>	10



Fully insulated connector for tapping into a line without stripping the insulation. No special tools are required.




Place wire to be tapped in locating notch. Then close with pliers.




Complete connection with Auveco fully insulated male terminal:  
11828 (22-18 ga.),  
11605 (16-14 ga.) or  
11830 (12 ga.)


### Specialty Terminal - Vinyl Insulated

	1/4" Tab 16-14 Ga.	<b>12158</b>	25
---	-----------------------	--------------	----


### Fuse Block Accessory Clip

	For Add-on Electrical Equipment	<b>11405</b>	50
--	---------------------------------------	--------------	----

### Blade Type Fuse Tap

  Refer To Page 173.	For tapping "hot side" of fuse block	<b>14474</b>	25
---	--	--------------	----

### Mini Fuse Blade Type Fuse Tap

  Refer To Page 173.	For tapping "hot side" of mini fuse type fuse block	<b>17686</b>	50
--	---	--------------	----