

## Sec. 12

# Sealed Crimp & Solder Terminals & Connectors

Crimped for mechanical reliability, soldered for superior strength and conductivity, and sealed with heat shrink tubing for maximum durability.

### THE CRIMP CONNECTOR

There are crimp indicators which show where the installation tool should be positioned

Wire-stops in butt connectors prevent over-insertion of the wire

Window in the connector allows for visual inspection & solder to flow into

### THE SOLDER

Flux coating to clean metal surfaces










Low-temperature solder alloy for ease of installation









Pre-measured solder to provide the right amount of solder to ensure a solid termination

### THE HEAT SHRINK TUBING

Adhesive lined polyolefin to seal the connection

Translucent tubing to allow for visual inspection

Actual Size	Stud Size	Auveco Part No.	U.P. Qty
<b>24-22 Gauge Wire Range (Clear)</b>			
	Butt Connector	<b>21002</b>	10
<b>20 - 18 Gauge Wire Range (Red)</b>			
	#8	<b>21260</b>	10
	#10	<b>21261</b>	10
	1/4"	<b>21262</b>	10
	5/16"	<b>21263</b>	10
	3/8"	<b>21264</b>	10
	1/4" Female Slip-On	<b>21278</b>	10
	1/4" Male Slip-On	<b>21279</b>	10
	Butt Connector	<b>21003</b>	10
Step Down Butt Connector	24 - 22 Ga. To 20 - 18 Ga.	<b>21275</b>	10

Actual Size	Stud Size	Auveco Part No.	U.P. Qty
<b>16 - 14 Gauge Wire Range (Blue)</b>			
	#8	<b>21265</b>	10
	#10	<b>21266</b>	10
	1/4"	<b>21267</b>	10
	5/16"	<b>21268</b>	10
	3/8"	<b>21269</b>	10
	1/4" Female Slip-On	<b>21280</b>	10
	1/4" Male Slip-On	<b>21281</b>	10
	Butt Connector	<b>21004</b>	10
Step Down Butt Connector	20-18 Ga. To 16-14 Ga.	<b>21276</b>	10