


Sec. 12

HEAT SHRINK TUBING

Made In The U.S.A.



Black Thin Wall Heat Shrink Tubing

- 2 To 1 Shrink Ratio
- Highly Flame Retardant (VW-1)
- Cross linked Polyolefin

Auveco Part No.	Pre-Shrink Size	Pre-Shrink I.D.	Post-Shrink I.D.	Post-Shrink Length	Unit Pkg.	Auveco Part No.	Pre-Shrink Size	Pre-Shrink I.D.	Post-Shrink I.D.	Post-Shrink Length	Unit Pkg.
18693	3/64"	.046"	.023"	.6"	25	18699	3/8"	.375"	.187"	.6"	15
18694	1/16"	.063"	.031"	.6"	25	18700	1/2"	.500"	.250"	.6"	15
18695	3/32"	.093"	.046"	.6"	25	18701	3/4"	.750"	.375"	.6"	10
18696	1/8"	.125"	.062"	.6"	25	18702	1"	1.00"	.500"	.6"	10
18697	3/16"	.187"	.093"	.6"	25	18703	1-1/2"	1.50"	.750"	.6"	5
18698	1/4"	.250"	.125"	.6"	25	18704	2"	2.00"	1.00"	.6"	5

Adhesive Lined Heat Shrink Tubing

- 4.5 To 1 Shrink Ratio
- Cross linked, Semi-Rigid Polyolefin Outer Jacket
- Hot-Melt Adhesive Inner Wall Adheres To All Major Types Of Wire
- Environmentally Seals & Insulates
- Meets O.E.M. Specs: Ford: ESB M99 D56 A1 Chrysler: MS-DB56

Auveco Part No.	Pre-Shrink I.D.	Post-Shrink I.D.	Length	Color	Unit Pkg.
18705	.225"	.050"	3-1/2"	Black	10
18706	.293"	.065"	3-1/2"	Black	10
18707	.427"	.095"	3-1/2"	Black	10
18708	.700"	.175"	3-1/2"	Black	5

Adhesive Lined Dual Wall Self-Sealing Heat Shrink Tubing

- 3 To 1 Shrink Ratio
- Provides Waterproofing & Environmental Protection
- Excellent Insulating, Abrasion-Resisting & Strain Relief Properties

Part No.	Size	I.D.	I.D.	Length	Color	Pkg.
16665	22-14 Ga.	.188"	.062"	.12"	Black	4
16666	12-10 Ga.	.250"	.083"	.12"	Black	4
18733	14-10 Ga.	.400"	.150"	.6"	Black	4
19102	14-10 Ga.	.400"	.150"	.6"	Black	25
18734	14-10 Ga.	.400"	.150"	.6"	Red	4
19103	14-10 Ga.	.400"	.150"	.6"	Red	25
18735	8-1 Ga.	.750"	.220"	.6"	Black	4
19104	8-1 Ga.	.750"	.220"	.6"	Black	25
18736	8-1 Ga.	.750"	.220"	.6"	Red	4
19105	8-1 Ga.	.750"	.220"	.6"	Red	25
18737	2-4/0 Ga.	1.100"	.375"	.6"	Black	4
19106	2-4/0 Ga.	1.100"	.375"	.6"	Black	25
18738	2-4/0 Ga.	1.100"	.375"	.6"	Red	4
19107	2-4/0 Ga.	1.100"	.375"	.6"	Red	25

Part No. 18887

Six inch lengths of black thin wall, cross linked polyolefin, heat shrink tubing in a durable translucent polypropylene box. The tubing has 2:1 shrink ratio.



Part No.	Qty.	Size	Pre-Shrink I.D.	Post-Shrink I.D.
18697	36	3/16"	.187"	.093"
18698	24	1/4"	.250"	.125"
18699	12	3/8"	.375"	.187"
18700	6	1/2"	.500"	.250"
18701	4	3/4"	.750"	.375"
18702	4	1"	1.00"	.500"

UNIT PACKAGE: 1