



**Metric Hex Socket Head Cap Screws**

DIN 912

Regular Pitch - Grade 12.9

Heat Treated Alloy Steel • Plain Finish

Tensile Strength: 177,000 PSI

Auveco Part No.		Diameter & Pitch	Length
Unit Package			
10	100		
<b>10845</b>	<b>10872</b>	4mm-.7	12mm
<b>10846</b>	<b>10873</b>	5mm-.8	12mm
<b>10848</b>	<b>10875</b>	5mm-.8	20mm
<b>10851</b>	<b>10878</b>	6mm-1.00	16mm
<b>10853</b>	.....	6mm-1.00	25mm
<b>10854</b>	.....	6mm-1.00	30mm
<b>10855</b>	.....	8mm-1.25	16mm
<b>10858</b>	<b>10885</b>	8mm-1.25	30mm
<b>10859</b>	.....	8mm-1.25	35mm
<b>10861</b>	.....	10mm-1.50	20mm
<b>10863</b>	.....	10mm-1.50	30mm
<b>10864</b>	.....	10mm-1.50	40mm
<b>10865</b>	.....	10mm-1.50	50mm
<b>10866</b>	.....	12mm-1.75	30mm
<b>10867</b>	.....	12mm-1.75	35mm
<b>10868</b>	.....	12mm-1.75	40mm
<b>10870</b>	.....	12mm-1.75	60mm



**Metric Low Socket Head Cap Screws**

DIN 6912

Regular Pitch - Grade 8.8

Heat Treated Alloy Steel • Plain Finish

Tensile Strength: 116,000 PSI

Auveco Part No.	Unit Pkg.	Diameter & Pitch	Length
<b>10898</b>	10	5mm-.8	10mm

**All items available in bulk.**

**Please Order  
In Unit Package Quantities  
Not Number Of Pieces**



**Metric Flat Head Socket Cap Screws**

DIN 7991

Regular Pitch - Grade 10.9

Heat Treated Alloy Steel • Plain Finish • Tensile Strength: 150,800 PSI

Auveco Part No.		Diameter & Pitch	Length
Unit Package			
10	100		
<b>10960</b>	<b>10961</b>	6mm-1.00	16mm

Auveco Part No.	Unit Package	Diameter & Pitch	Length
<b>10970</b>	10	8mm-1.25	20mm
<b>10972</b>	10	8mm-1.25	25mm