

NUTS

Sec. 8

Finished USS (Coarse) & SAE (Fine) Hexagon Nuts Zinc Plated



Auveco Part No.	Thread Size	Hex Width	Unit Pkg.	Auveco Part No.	Thread Size	Hex Width	Unit Pkg.
3541	1/4"-20 USS	7/16"	100	3549	1/2"-13 USS	3/4"	100
3542	1/4"-28 SAE	7/16"	100	3550	1/2"-20 SAE	3/4"	100
3543	5/16"-18 USS	1/2"	100	8659	9/16"-12 USS	7/8"	50
3544	5/16"-24 SAE	1/2"	100	8660	9/16"-18 SAE	7/8"	50
3545	3/8"-16 USS	9/16"	100	8661	5/8"-11 USS	15/16"	50
3546	3/8"-24 SAE	9/16"	100	8662	5/8"-18 SAE	15/16"	50
3547	7/16"-14 USS	11/16"	100	8663	3/4"-10 USS	1-1/8"	50
3548	7/16"-20 SAE	11/16"	100				

Grade 5 Finished USS (Coarse) & SAE (Fine) Hex Nuts



Fully Certified For
S.A.E. J995 Standard
Proof Load: 120,000 PSI
C32 Max. Rockwell Hardness
Zinc Plated

Auveco Part No.	Thread Size	Hex Width	Unit Pkg.	Auveco Part No.	Thread Size	Hex Width	Unit Pkg.
15586	1/4"-20 USS	7/16"	100	15590	1/2"-13 USS	3/4"	50
15595	1/4"-28 SAE	7/16"	100	15599	1/2"-20 SAE	3/4"	50
15587	5/16"-18 USS	1/2"	100	16981	9/16"-12 USS	7/8"	25
15596	5/16"-24 SAE	1/2"	100	15591	5/8"-11 USS	15/16"	25
15588	3/8"-16 USS	9/16"	100	15600	5/8"-18 SAE	15/16"	25
15597	3/8"-24 SAE	9/16"	100	15592	3/4"-10 USS	1-1/8"	25
15589	7/16"-14 USS	11/16"	50	15601	3/4"-16 SAE	1-1/8"	25
15598	7/16"-20 SAE	11/16"	50	15594	1"-8 USS	1-15/32"	10